

DS-D5032FL 32" Monitor

Overview

DS-D5032FL is a reliable surveillance display with LED backlit technology, excellent color reduction and image processing, truly display the video details. Multiply interfaces are able to meet various surveillance environments, and build-in speaker is convenient to audio play. DS-D5032FL is an ideal choice for security and surveillance application.



Key Features

- LED backlit technology with full HD 1920 x 1080
- Wide view angle: 178°(H)/178°(V)
- Image processing: 3D comb filter, 3D De-interlace, 3D noise reduction, Skin correction
- Multiply inputs: HDMI, VGA, DVI, BNC, USB, audio in
- Build-in speaker
- Image freeze
- High reliable components for 7 x 24 working
- VESA stand bracket

Model

DS-D5032FL

Interfaces



Interfaces	Description
HDMI	HDMI Digital Signal Input
DVI IN	DVI Digital Signal Input
VGA IN	VGA Analog Signal Input
CVBS/IN	Composite Video Input
USB	USB Interface
AUDIO IN	Audio Input
AUDIO OUT	Audio Output
RS232 IN	Serial Input



DS-D5032FL 32" Monitor



Specification

Model	DS-D5032FL
Display	
Display Type	LED-Backlit TFT LCD
Screen Size	32"
Pixel Pitch(H×V)	0.3637 mm × 0.3637 mm
Max Resolution	1920 x 1080
Brightness	400 cd/m ² (Typical)
Contrast	3000 : 1
Response Time	6.5 ms
Color	16.7 M
Viewing Angle	Horizontal 178°, Vertical 178°
Input	
HDMI	HDMI x 1
VGA	VGA x 1
DVI	DVI x 1
BNC	BNC x 1
USB	USB x 1
Audio	
Audio Input	1, 3.5 mm mini-jack
Audio Out	1, 3.5 mm mini-jack
Speaker	3W x 2
Mounting	
VESA	200 mm x 200 mm
General	
Power Supply	AC100 ~ 240 V, 50 / 60 Hz
Consumption	< 60W(on) < 1W(Standby)
Operation Temperature	0°C ~ 40 °C
Operation Humidity	10%~85% (No Condensation)
Storage Temperature	-20°C ~ 60°C
Storage Humidity	10%~90% (No Condensation)
Dimension (W×H×D)	737.4 mm × 452.5 mm × 70.65 mm (29.03" x 17.81" x 2.78")
Weight	19 Kg(Gross weight) ,12 Kg (Net weight)
Included Accessories	Remote control x 1, battery x 2, power cord x 1, user manual x 1, warranty card x 1, CD x 1

DS-D5032FL 32" Monitor



Dimension (mm)

