

CU-7060-B

Column Speaker



Description

The CU-7000 series is an indoor column speaker specialized for places where rich sound pressure and high quality music reproduction are required. Designed to minimize driver-to-driver interference, it delivers clear and rich sound with high-frequency and low-loss professional-quality audio. It is suitable for indoor space such as churches, religious facilities, hotel lobby, restaurant, etc.

Technical Specifications

Model		CU-7060
Type		Dual 4" 2Way Column Speaker
LF Driver		4"x 2
HF Driver		0.5"x 1
Power Handling (AES)		60W
Input Power	100V	60/30W
Impedance	100V	166/330Ω
	LOW	8Ω
Power Selection		By Terminal
Frequency Range(-10dB)		100Hz ~ 20kHz
Frequency Range(-20%)		55Hz ~ 20kHz
Sensitivity (1W/1m, 1kHz)		92dB
Maximum SPL[Cont]		111dB
Nominal Dispersion(HxV)	1kHz	140° / 100°
	4kHz	180° / 106°
Input Connection		4P Screw Terminal
Enclosure Material		15T MDF Polyurea Coating
Enclosure Color		Black
Grille Material		EGI 0.8T
Grille Color		Black
Weight (Net)		5.42kg
Dimensions (Net, WxHxD, mm)		130 x 420 x 195
Included Accessories		Wall Bracket