

WS-15T/W-30T/W-50T/W- 80T/W

Indoor/outdoor compact wall mount speakers 15-30-50-80W - 8Ω - white

WS-15T/B-30T/B- 50T/B- 80T/B: WS-15/W-30T/W- 50T/W- 80T/W black editions



WS-50T/W



WS-15T/B



WS-30T/B




WS-50T/B



WS-80T/B

- All new WS Series is the Installation Speaker which is weather resistant and it also brightens the venue with its elegant design. The speakers can be used in various applications from small-sized venues to mid/large-sized venues. To be specific, it particularly fits in facilities that high quality of background music is playing a crucial role (cafes and hotel lobby etc.), educational facilities (auditorium and conference room etc.) and cultural facilities (exhibition hall etc.)
- WS Series is composed of 4 models from 2.5" Full-Range unit installed compact-sized WS-15T to 6.5" 2way model WS-80T.
- The Series has been applied with newly developed Full-Range unit, HF driver and LF driver unit to provide high-power clear sound without distortion. Moreover, 2way model adopts asymmetric horn design to over audience area perfectly.
- With the speaker taps on the rear panel of the every WS Series model, 100 V line/70 V line and low impedance (8 Ω) output can be adjusted.
- WS Series has obtained IP rate of 54 which enables to be used in various indoor and outdoor applications.



Model		WS-15T	WS-30T	WS-50T	WS-80T
Type		2.5" 1 way full range	4" 2 way passive	5" 2 way passive	6.5" 2 way passive
Enclosure Material		ABS RESIN			
Power Rating	Continuous (AES Std)	15W	30W	50W	80W
	Program: +3dB	30W	60W	100W	160W
	Peak: +6dB	60W	120W	200W	320W
Nominal Impedance		8Ω			
Bandwidth (-10 dB)		110 Hz~20 kHz	100 Hz ~20 kHz		
Sensitivity 1W / 1m (dB)		84	85	87	90
SPL Max		102dB	106dB	110dB	115dB
Directivity (1 kHz)		90°	Horizontal: 120° (Near Field) , 60° (Far Field) Vertical: +20° to -40° (on axis)		
Transformer Taps	70 V	15/10/5/3W	30/15/7.5/3.8/1.9W	50/25/13/6.5/3.3W	80/40/20/10/5W
	100 V	15/10/5/3W	30/15/7.5/3.8W	50/25/13/6.5W	80/40/20/10/5W
Connectors		WAGO type quick lever bollards			
Operating temperature		-15°C to + 55°C			
Dimensions (WxHxD) (mm)		92x120x114	139x210x129	173x250x150	210x311x169
Weight (kg)		0.9	1.72	2.37	3.57
Protection Index		IP54, IK08			
Availabilities		MTTF: 150.000 hours - MTTR: 5 minutes			

MAJORCOM:

56, chemin de la Flambère · 31300 Toulouse · FRANCE · Tél. 33 (0)5 61 31 86 87
Fax 33 (0)5 61 31 87 73 · commercial@majorcom.fr · www.majorcom.fr