

EVA 10P+SFP MAN

Industrial Gigabit Smart Managed Switch with 2 SFP ports

Product Highlights

Robust Design

High EMC endurance, fanless design, and wider operating temperature range combined with an IP30 housing to withstand harsh operating environments.

Flexible Deployment

Small form design that supports multiple mounting types to allow for flexible and swift deployment.

Powerful Management

Features a variety of flexible management options including a web-based UI, industry-standard CLI, SNMP, and a dedicated RJ-45 console port.



Features

Flexible Availability

- Industrial model variations with wider operating temperature ranges

Robust and High-Redundancy Design

- Fanless, passive cooling design
- High EMC endurance
- Built-in 6 kV surge protection on copper ports
- Ethernet Ring Protection Switching (ERPS)
- Dual power input for redundant power supplies
- Shock - IEC 60068-2-27, Freefall - IEC 60068-2-32, Vibration - IEC 60068-2-6 certified

Layer 2 Features

- IEEE 802.1Q and port-based VLAN
- IEEE 802.1p Quality of Service (QoS)
- STP/RSTP/MSTP
- Port mirroring
- Link aggregation
- Bandwidth control
- Broadcast storm control
- IGMP/MLD Snooping

Advanced Features

- Auto-Surveillance VLAN 2.0 (ASV 2.0)

The EVA 10P+SFP MAN Industrial Gigabit Smart Managed Switch is equipped with 10 x10/100/1000BASE-T ports and 2 x SFP ports. The switch features a robust design making it ideal for deployment in industrial and outdoor cabinet, capable of withstanding harsh environments. The EVA 10P+SFP MAN switch furthermore integrates advanced management and security functions to provide a complete industrial networking solution.

Durable and Reliable Design

The EVA 10P+SFP MAN switch is housed in a highly resistant IP30-rated metal casing to protect it from harsh environmental conditions and withstand wide temperature range, vibrations and shock. The high electromagnetic compatibility (EMC) protects the switch from unwanted effects when operating in environments with strong electromagnetic interference.

Meanwhile, the fanless design extends the life of the EVA 10P+SFP MAN switch while also being able to operate in a wider temperature range of up to 65 °C. For increased flexibility, the switch can be mounted on a DIN rail or wall-mounted.

Additionally, the EVA 10P+SFP MAN switch features high-capacity 6 kV surge protection on all copper ports to help prevent damage to the switch and connected devices caused by sudden power surges and lightning strikes. The built-in surge protection of up to 6 kV can mitigate the damage to the switch from both indoor and outdoor devices and network connections by absorbing the excess energy while still letting through the amount of power required for the switch to operate normally. This increases network reliability, reduces repair costs, and removes the need for replacement hardware in the event of an electrical surge or lightning strike.

EVA 10P+SFP MAN

Industrial Gigabit Smart Managed Switch with 2 SFP ports

Product Highlights

Robust Design

High EMC endurance, fanless design, and wider operating temperature range combined with an IP30 housing to withstand harsh operating environments.

Flexible Deployment

Small form design that supports multiple mounting types to allow for flexible and swift deployment.

Powerful Management

Features a variety of flexible management options including a web-based UI, industry-standard CLI, SNMP, and a dedicated RJ-45 console port.



Features

Flexible Availability

- Industrial model variations with wider operating temperature ranges

Robust and High-Redundancy Design

- Fanless, passive cooling design
- High EMC endurance
- Built-in 6 kV surge protection on copper ports
- Ethernet Ring Protection Switching (ERPS)
- Dual power input for redundant power supplies
- Shock - IEC 60068-2-27, Freefall - IEC 60068-2-32, Vibration - IEC 60068-2-6 certified

Layer 2 Features

- IEEE 802.1Q and port-based VLAN
- IEEE 802.1p Quality of Service (QoS)
- STP/RSTP/MSTP
- Port mirroring
- Link aggregation
- Bandwidth control
- Broadcast storm control
- IGMP/MLD Snooping

Advanced Features

- Auto-Surveillance VLAN 2.0 (ASV 2.0)

High Redundancy and Reliability

The EVA 10P+SFP MAN switch supports ERPS quick failover recovery for ring topologies that ensures minimal downtime and avoids any loss of data in mission-critical deployment settings. Meanwhile, the dual power input allows for a redundant power supply to make sure the device continues to operate in the event of a primary power supply failure.

Surveillance Traffic Optimisation

The EVA 10P+SFP MAN switch supports the Auto-Surveillance VLAN (ASV) feature. This automatically detects surveillance devices and puts them into a dedicated surveillance VLAN, segmenting this type of traffic from the rest of the network. This provides increased security of surveillance data, and gives the traffic a higher priority through the switch, minimising the disruption or delays on video streams. A single switch can be used for both surveillance and data networks, removing the need for dedicated surveillance hardware while simultaneously reducing maintenance costs.

Easy Troubleshooting

The EVA 10P+SFP MAN switch features loopback detection and cable diagnostics to help network administrators find and solve network problems quickly and easily. Loopback detection is used to detect loops created by a specific port and automatically shuts down the affected port. Cable diagnostics helps network administrators quickly examine the quality of the copper cables, recognize the cable type, and detect cable errors.

EVA 10P+SFP MAN

Industrial Gigabit Smart Managed Switch with 2 SFP ports

TECHNICAL CHARACTERISTICS

General	EVA 10P+SFP MAN
Number of Ports	<ul style="list-style-type: none">• 10 x 10/100/1000BASE-T ports• 2 x SFP ports• 1 x RJ-45 Console port
Port Functions	<ul style="list-style-type: none">• IEEE 802.3 for Ethernet• IEEE 802.3u for Fast Ethernet• IEEE 802.3ab for Gigabit Ethernet• IEEE 802.3z for Gigabit fibre• IEEE 802.3az-compliant
Media Interface Exchange	Auto-MDI/MDIX adjustment for all twisted pair ports
Performance	
Switching Capacity	24 Gbps
Maximum Forwarding Rate	17.85 Mpps
MAC Address Table Size	Up to 8K entries
Transmission Method	Store-and-forward
Physical	
Diagnostic LEDs	SYS, ALM, PWR1/2/3, Link/Activity/Speed
Power Input	<ul style="list-style-type: none">• 12 to 48 V DC terminal block dual input• 12 V DC 4-pin DIN single power input
Power Consumptions	<ul style="list-style-type: none">• Maximum: 10.26 W• Standby: 5.94 W
Alarm Relay	1 A at 24 V
Heat Dissipation	35.01 BTU/hr
Weight	1.63 kg
Dimensions	210 x 171.2 x 53 mm
Ventilation	Fanless
Operating Temperature	-40 to 65 °C
Storage Temperature	-40 to 85 °C
Operating Humidity	0% to 95% RH, non-condensing
Storage Humidity	0% to 95% RH, non-condensing
Material	IP30-rated metal casing
Installation	DIN rail/wall mountable
MTBF	276,773 hours
Certifications	CE, FCC, BSMI
Safety	UL60950-1
EMI	CISPR 22, FCC Part 15B Class A
EMS	EN 61000-4-2 ESD, EN 61000-4-3 RS, EN 61000-4-4 EFT, EN 61000-4-5, EN 61000-4-6 CS, EN 61000-4-8
Environmental Tests	IEC 60068-2-27 Shock, IEC 60068-2-32 Freefall, IEC 60068-2-6 Vibration

EVA 10P+SFP MAN

Industrial Gigabit Smart Managed Switch with 2 SFP ports

Software Features		
VLAN	<ul style="list-style-type: none">• IEEE 802.1Q tagged VLAN• Port-based VLAN• Auto-Surveillance VLAN 2.0 (ASV 2.0)• Voice VLAN• Asymmetric VLAN	<ul style="list-style-type: none">• VLAN group :<ul style="list-style-type: none">• Supports 128 static VLAN groups• Max. 4094 VIDs• GVRP
L2 Features	<ul style="list-style-type: none">• Flow Control :<ul style="list-style-type: none">• IEEE 802.3x Flow Control• HDL Blocking Prevention• Jumbo frames up to 9600 bytes• IGMP Snooping :<ul style="list-style-type: none">• IGMP v1/v2/v3• Supports up to 256 IGMP snooping groups (shared with MLD snooping)• IGMP Snooping Querier• MLD Snooping :<ul style="list-style-type: none">• MLD snooping v1/v2• Supports up to 256 MLD snooping groups (shared with IGMP snooping)• MLD Snooping Querier• IEEE 802.3ad Link Aggregation :<ul style="list-style-type: none">• Supports 6 groups per device, 8 ports per group• Ethernet Ring Protection Switching (ERPS) :<ul style="list-style-type: none">• G.8032 ERPSv1 single ring	<ul style="list-style-type: none">• Loopback detection• LLDP• Port mirroring :<ul style="list-style-type: none">• One-to-One• Many-to-One• Statistics :<ul style="list-style-type: none">• Tx Ok• Tx Error• Rx Ok• Rx Error• Spanning Tree Protocol (STP) :<ul style="list-style-type: none">• IEEE 802.1D STP• IEEE 802.1w RSTP• IEEE 802.1s MSTP
Quality of Service (QoS)	<ul style="list-style-type: none">• IEEE 802.1p Quality of Service (QoS) :<ul style="list-style-type: none">• 4 queues per port• Queue handling• Strict Priority Queue (SPQ)• Weighted Round Robin (WRR)• Port-based bandwidth control (rate limiting)• Ingress: 100 kbps	
Security	<ul style="list-style-type: none">• D-Link Safeguard• Traffic segmentation• Broadcast/Multicast/Unknown Unicast Storm Control• DoS attack prevention	<ul style="list-style-type: none">• SSL• SSH• Port security
AAA	<ul style="list-style-type: none">• IEEE 802.1x Port-based access control• Web-based access control	<ul style="list-style-type: none">• RADIUS
Management	<ul style="list-style-type: none">• Web-based UI (supports IPv4/IPv6)• Client-based D-Link Network Assistant (DNA)• Industry-standard CLI• SNMP• SNMP v1/v2c/v3• SNMP trap• Telnet server	<ul style="list-style-type: none">• System Log• DHCP client• TFTP client• LLDP• D-Link Discovery Protocol (DDP)• Dual images• Dual configurations
OAM	<ul style="list-style-type: none">• Cable diagnostics	<ul style="list-style-type: none">• Optical transceiver Digital Diagnostics Monitoring (DDM)
Green Technology	<ul style="list-style-type: none">• Power saving by:<ul style="list-style-type: none">• Link status detection• LED shut-off• Port shut-off• System hibernation• IEEE 802.3az Energy-Efficient Ethernet (EEE)	
MIB/RFC Standards	<ul style="list-style-type: none">• RFC768 UDP• RFC791 IP• RFC792 ICMP• RFC793 TCP• RFC826 ARP• RFC1213 MIB II• RFC1493 Bridge MIB	<ul style="list-style-type: none">• RFC1907 SNMPv2 MIB• RFC2668 802.3 MAU MIB• RFC4133 Entity MIB• RFC4363 IEEE 802.1p MIB• ZoneDefense MIB• Private MIB