

P 860T VA

2-Way Ceiling Speaker 60 W

FEATURES

- P 860T VA is a 2 way bass reflex ceiling speaker suitable for high quality installation.
- Fitted with a 8" speaker, a neodymium tweeter and a 100V transformer with 4 power taps, it offers a very high sound quality.
- Easy installation via screw mounting system.




EN 54 24

TECHNICAL CHARACTERISTICS

MODEL		P 515T VA							
Power	Dimensions (LxWxH)	Weight	Color	Sensitivity (1W/4W) EN 54-24	Frequency response (Hz)	Directivity 500 Hz	Directivity 1 kHz	Directivity 2 kHz	Directivity 4 kHz
60 / 30 / 15 / 7,5 W	Ø 320 x P 254 mm	4.7 kg	RAL 9016	79.2 dB	50 > 24 K	180°	165°	130°	80°

MOUNTING INSTRUCTIONS

1. Connect the connecting cable to the Phoenix terminal and plug it into the pin header of the loudspeaker.
2. Attach the strain relief to the connection cable.
3. Mount the loudspeaker flush in the ceiling cut-out (302mm) and tighten the four mounting screws behind the grille.
4. To adjust the power, remove the grille, set the the desired adjustment at the rotary switch and attach the grille back up.

 n° 1438 22 Certificate n° : 1438-CPR-0854	EN 54-24 Speaker for voice alarm systems for systems for fire detection systems and fire alarm systems in buildings
	P 860T VA Type A