

PSUB 120T

Ceiling Subwoofer 120 W

FEATURES

EN 54 24

- This 120W powered subwoofer is equipped with a 200mm high-performance system featuring 4 power adjustments 120/60/30/15W.
- PSUB 120T offers an amazing deep bass response which gives your voice alarm installation a rich sound quality.
- Power tapings are easily set at the front of the speaker, a low impedance operation at 4ohm is also possible. The crossover frequency is set to 135 Hz. You can change the phase 180° by a switch at the front. To make things perfect the metal housing in RAL 9016 guarantees long-term durability.
- Protection class IP 21C secures the speaker against the risks of environmental influences. The speaker chassis is impregnated against wetness. Easy installation via screw mounting system. Perfectly suitable for installations where high sound quality is demanded.



TECHNICAL CHARACTERISTICS

MODEL	PSUB 120T								
Power	Dimensions (LxWxH)	Weight	Color	Sensitivity (1W/4W) EN 54-24	Frequency response (Hz)	Directivity 500 Hz	Directivity 1 kHz	Directivity 2 kHz	Directivity 4 kHz
120 / 60 / 30 / 15 W - 4 Ω	Ø 319 x 250 mm	6,4 kg	RAL 9016	75 dB	32 > 280 K	-	-	-	-

MOUNTING INSTRUCTIONS

1. Open the terminal cover (metal plate) on the rear side of the speaker.
2. Put the connecting cable through the grommet of the metal plate.
3. Connect the wiring to the removeable 4-pole connector and tighten the cabling by the screws.
4. Plug the connector into the socket at the rear side of the speaker.
5. Fix the metal plate by turning the screws.
6. Remove the speaker grille by using the attached mounting hook.
7. Insert the speaker into the ceiling until the front baffle rim touches the ceiling. Turn the attachment screws to tighten the mounting tabs. Put the grille back on the speaker.