

# IP-1015BX

## Network Audio Bridge Amplifier

- Built-in 10W Class-D amplifier
- Supports PoE/PoE+
- Ethernet 10/100 BASE-T (default IP: 192.168.1.99)
- Micro SD card slot



Model	IP-1015BX
<b>AMPLIFIER</b>	
Rated output power (8Ω,1kHz sine wave)	3,7W (PoE), 10W (PoE+)
Frequency response (1W @ 8Ω, ±1dB)	20Hz - 20kHz
THD+N (20Hz HPF, AES17 LPF, 8Ω)	< 3%
<b>LINE OUTPUT (X 1)</b>	
Maximum audio output (balanced)	+6dBV ±3dB
Frequency response	20Hz - 20kHz (+1/-3dB)
THD+N (20Hz HPF, AES17 LPF)	< 0,1%
S/N (20Hz HPF, AES17 LPF, A-WTD)	> 85dB
<b>CONTACT I/O</b>	
Contact Input (1CH)	Dry contact
Contact Output (1CH)	Dry contact (N.O: Normally open)
<b>STORAGE</b>	
Memory	Internal: 1Go / External: MicroSD Max 32Go
<b>NETWORK</b>	
Ethernet	10/100 Base-TX
<b>GENERAL</b>	
Power	PoE (IEEE 802.3af type 1 Class 3) / PoE+ (IEEE 802.3at type 2 Class 4)
Operating temperature	-20°C ~ +50°C
Power consumption	PoE (IEEE 802.3af) : 44-57 VDC, Max 12,95W PoE+ (IEEE 802.3at): 50-57 VDC, Max 25,5W
Dimensions (WxHxD)	123 x 80 x 30,6mm
Weight	0,24kg