

IP-1015HS

Network horn speaker

- All-in-one speaker system
- 10W Class-D amplifier integrated
- PoE/PoE+ support
- Ethernet 10/100 BASE-T (Default IP: 192.168.1.99)
- VoIP, background music, scheduler, TTS



Model	IP-1015HS
SPEAKER	
Type	Network Horn Speaker
Driver	1" Dome type (10W), V/C: 28mm, 8Ω
SPL Max	121dB (PoE 802.3af) / 124dB (PoE+ 802.3at)
Frequency Range	300Hz~5.5kHz
Nominal Dispersion(HxV)	1kHz : 110° x 140° / 4kHz : 60° x 70°
Enclosure	Material: ABS, Aluminium
AMPLIFIER	
Rated output power	3.7W (PoE 802.3af), 10W (PoE+ 802.3at)
MIC	
Embedded mic	50Hz ~ 16kHz
LINE OUTPUT	
Maximum audio output	-
Frequency response	-
THD+N (20Hz HPF, AES17 LPF)	-
S/N (20Hz HPF, AES17 LPF, A-WTD)	-
CONTACT I/O	
Contact Input (1CH)	Dry contact
Contact Output (1CH)	Dry contact (N.O: Normally open)
NETWORK	
Ethernet	10/100 Base-TX
GENERAL	
Power	PoE (IEEE 802.3af type 1 Class 3) / PoE+ (IEEE 802.3at type 2 Class 4)
Operating temperature	-40°C ~ +60°C
Protection	IP66
Power consumption	PoE (IEEE 802.3af) : 44~57 VDC, Max 12.95W PoE+ (IEEE 802.3at) : 50~57 VDC, Max 25.5W
Connector	Ethernet Jack (RJ-45)
Dimensions (WxHxD)	250 x 166 x 305mm
Weight	2.4kg