

DL-SE 20-200/T+ EN54

2-Way Ceiling Speaker

20 W

FEATURES

EN 54 24

- 2-way ceiling speaker for Voice Alarm, 20W power, certified EN 54-24.
- The frameless design of this 2-way loudspeaker is inspired by the look of contemporary LED lights.
- The 20W powered speaker is equipped with a 200mm full-range loudspeaker and a 100V transformer with 3 power adjustments.
- The powder-coated metal housing in RAL 9016 guarantees long-term stability. For additional reliability, the speaker is impregnated against wetness.
- The speaker is also secured with protection class IP 21C against the security risks of environmental influences.
- Fast and easy installation through WAGO 221 connector and strong spring clamps with protective caps for vibration damping.
- The fire dome is included in the delivery.
- This speaker is suitable for a ceiling strength of approx. 1-45 mm.



TECHNICAL CHARACTERISTICS

MODEL	DL-SE 20-200/T+ EN54								
Power	Dimensions	SPL EN54-24, Pmax/4m	SPL IEC268- 5, 1W/1m	Frequency Response	Frequency Range	Sensitivity EN54-24, 1W/4m	Sensitivity EN54-24, 1W/1m	Dispersion -6dB, 4KHz	Dispersion -6dB, 2KHz
20/10/5 W	265 x 115 mm	93,9 dB	96,8 dB	47 - 22.000 Hz	60 - 20.050 Hz	81,1 dB	93,1 dB	47°	77°

MOUNTING INSTRUCTION

1. Create the necessary ceiling cut-out and check the installation depth.
2. Loosen the screws of the terminal cover, slide it to the right and remove the cover.
3. Guide the speaker cable through the cable gland of the terminal cover.
4. Connect the speaker cables to the WAGO terminal.
5. Put the terminal cover back on the rear of the speaker and slide the cover to the left. Tighten the screws again.
6. Fold up the speaker's leg springs and insert the speaker into the ceiling cut-out until it is flush with the ceiling.

Power Tappings	
Black	COM
Red	20 W
White	10 W
Green	5 W

 Certificate n° : 1438-CPR-0642 ic audio GmbH, Boehringerstraße 14a D-68307 Mannheim Germany	EN 54-24 Speaker for voice alarm systems for systems for fire detection systems and fire alarm systems in buildings
	DL-SE 20-200/T+ EN54
	Type A