

IG-1900

Counter intercom

KEY POINTS

- Ideal counters & ticket offices
- Console with embedded mic. & loudspeaker
- Robust all-in-one client-side module
- Quick and easy installation
- The counter intercom IG-1900 is ideal for closed counters or counters with glass/plexiglass protection.
- It facilitates the transmission of messages between interlocutors and guarantees intelligible communication in total safety.
- It also has intelligent audio functions such as active noise reduction and automatic sound level adjustment to ensure optimal exchange quality.
- It consists of a microphone console with integrated loudspeaker on the counter side (receptionist) and an all-in-one module with microphone and integrated



loudspeaker on the customer side.

- An AUX output also allows you to connect a magnetic induction loop, for example.

Model		IG-1900
Main console	Microphone type	Condensateur – Unidirectionnel
	Sensitivity	- 46 dB
	Frequency response	20 Hz - 16 kHz
	Embedded speaker	3 W (100Hz - 18kHz)
	Power supply	DC 12V 1.5A / Conso. ≤ 5W (Mains charger EU type C plug supplied)
	Temperature range	-10° / + 50°C
	Humidity range	≤ 90% RH
	Color	Silver
	Material	Steel
	Dimensions (l x p x h)	95 x 160 x 46.5mm
	Weight	440 g
Secondary unit Client's module	Microphone type	Electret - Unidirectional
	Sensitivity	- 46 dB
	Frequency response	20 Hz - 16 kHz
	Embedded speaker	3W (92 dB @ 1W / 1m) 100 Hz - 18kHz
	Power supply	Powered by main console
	Temperature range	-10° / + 50°C
	Humidity range	≤ 90% RH
	Color	Silver
	Material	Aluminium
	Dimensions (l x p x h)	87 x 25 x 87mm
	Weight	200 g

IG-1900

Counter intercom



Detailed dimensions

